

GASOLINE PORTABLE SERIES

ELECTRIC START ENGINE 3000 RPM

Air Cooled

3000 rpm

LWA
2000/14/CE

HONDA



G S A



G S A



G T A

	MGTP 4,8 H BM AE	MGTP 6,5 H BM AE	MGTP 7 H BT AE
Code	PP63-5M00	PP64-7M00	PP65-7T00
On board control panel equipped with:			
	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
Generator			
Type	Linz E1C10SF	Linz E1C10MH	Linz E1S10MH
Power	4,8 kVA 230V	6,5 kVA 230V	7 kVA 400V
Frequency	50 Hz	50 Hz	50 Hz
Engine			
	HONDA	HONDA	HONDA
Engine type	GX270	GX390	GX390
N° cylinders	1	1	1
Power	8,4 HP	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric	Electric
Dimensions & weight			
Fuel tank capacity	5,3 lt	6,4 lt	6,4 lt
Running Time	2,7 hrs	2 hrs	2 hrs
Dry weight	85 Kg	105 Kg	105 Kg
Dimensions (L. x W. x H.)	760 x 520 x 620 mm	760 x 520 x 620 mm	760 x 520 x 620 mm

Options

- ⊙ Site tow trailer
- ≡⊙ Road tow trailer
- ⊙ Trolley

Legend

G	Gasoline	S	Single phase	A	Air cooled
D	Diesel	T	Three phase	W	Water cooled