

Water Cooled

DIESEL

Three phase



1500 rpm



Noise level in compliance with directive 2000/14/CE

### DIESEL ENGINE DRIVEN GENERATING SET 1500 R.P.M.



#### DISTRIBUTION PANEL:

1x32 A 3Ph 400V EEC socket IP67
1x32 A 1Ph 230V EEC socket IP67
1x32 A 1Ph 230V EEC socket IP67

#### STANDARD FEATURES:

Built in fuel tank
Bunded tank
12V Battery
Forklift pocket
Central lifting eye
Exhaust gas silencer
Soundproof canopy

#### MGTP 130 SS FI

Code	IP147-130TS0	
<b>Generator</b>		
Type	Linz PRO22M E/4	
<b>Three phase power</b>	<b>130 kVA 400V</b>	
Frequency	Hz	50
Cosφ	0.8	
Insulation class	H	
Mechanical protection	IP23	
<b>Engine</b>		
Engine type	N67 TM1F	
N° cylinders	6	
Displacement	cm <sup>3</sup>	6700
Power	HP	173
Engine speed	r.p.m.	1500
Speed regulation	Mechanical	
Cooling	Water	
Fuel	Diesel	
Oil sump capacity	lt.	12
Starting system	Electric	
Specific fuel consumption	l/h	25
<b>Dimensions &amp; weight</b>		
Noise level	Lwa	90
Battery	V	12
Fuel tank capacity	lt.	400
Dry weight	Kg	2000
Dimensions (L. x W. x H.)	mm	3500 x 1200 x 2050

#### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310
ON/OFF switch
Safety cover for DSE 7310 and ON/OFF switch
Circuit breakers for sockets protection
Earth leakage relay as general protection
Emergency stop

#### Options

- Site tow trailer
- Road tow trailer