

Water Cooled

DIESEL

Three phase



1500 rpm



Noise level in compliance with directive 2000/14/CE

DIESEL ENGINE DRIVEN GENERATING SET 1500 R.P.M.



| MGTP 150 SS PI | | |
|---------------------------|---------------------|--------------------|
| Code | IP155-150TS0 | |
| Generator | | |
| Type | Linz PRO22M F/4 | |
| Three phase power | 150 kVA 400V | |
| Frequency | Hz | 50 |
| Cosφ | 0.8 | |
| Insulation class | H | |
| Mechanical protection | IP23 | |
| Engine | | |
| | | |
| Engine type | 1106D-E70TAG3 | |
| N° cylinders | 6 | |
| Displacement | cm ³ | 7000 |
| Power | HP | 184 |
| Engine speed | r.p.m. | 1500 |
| Speed regulation | Electronic | |
| Cooling | Water | |
| Fuel | Diesel | |
| Oil sump capacity | lt. | 16,5 |
| Starting system | Electric | |
| Specific fuel consumption | l/h | 29,7 |
| Dimensions & weight | | |
| Noise level | Lwa | 90 |
| Battery | V | 12 |
| Fuel tank capacity | lt. | 450 |
| Dry weight | Kg | 2070 |
| Dimensions (L. x W. x H.) | mm | 3600 x 1300 x 2150 |

ON BOARD CONTROL PANEL EQUIPPED WITH:

| |
|---|
| DSE 7310 |
| ON/OFF switch |
| Safety cover for DSE 7310 and ON/OFF switch |
| Circuit breakers for sockets protection |
| Earth leakage relay as general protection |
| Emergency stop |

DISTRIBUTION PANEL:

| |
|---------------------------------|
| 1x32 A 3Ph 400V EEC socket IP67 |
| 1x32 A 1Ph 230V EEC socket IP67 |
| 1x32 A 1Ph 230V EEC socket IP67 |

STANDARD FEATURES:

| |
|----------------------|
| Built in fuel tank |
| Bunded tank |
| 12V Battery |
| Forklift pocket |
| Central lifting eye |
| Exhaust gas silencer |
| Soundproof canopy |

Options

- Site tow trailer
- Road tow trailer