

Water Cooled

DIESEL

Three phase



1500 rpm



Noise level in compliance with directive 2000/14/CE

DIESEL ENGINE DRIVEN GENERATING SET 1500 R.P.M.



MGTP 20 SS PI	
Code	IP149-20TS0
Generator	
Type	Linz PRO18S A/4
Three phase power	20 kVA 400V
Frequency	Hz 50
Cosφ	0.8
Insulation class	H
Mechanical protection	IP23
Engine	
Engine type	404D-22G
N° cylinders	4
Displacement	cm ³ 2216
Power	HP 25
Engine speed	r.p.m. 1500
Speed regulation	Mechanical
Cooling	Water
Fuel	Diesel
Oil sump capacity	lt. 10,6
Starting system	Electric
Specific fuel consumption	l/h 4
Dimensions & weight	
Noise level	Lwa 90
Battery	V 12
Fuel tank capacity	lt. 130
Dry weight	Kg 730
Dimensions (L. x W. x H.)	mm 1750 x 900 x 1400

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 3110
ON/OFF switch
Safety cover for DSE 3110 and ON/OFF switch
Circuit breakers for sockets protection
Earth leakage relay as general protection
Emergency stop

DISTRIBUTION PANEL:

1x32 A 3Ph 400V EEC socket IP67
1x32 A 1Ph 230V EEC socket IP67
1x32 A 1Ph 230V EEC socket IP67

STANDARD FEATURES:

Built in fuel tank
Bunded tank
12V Battery
Forklift pocket
Central lifting eye
Exhaust gas silencer
Soundproof canopy

Options

- Site tow trailer
- Road tow trailer