

# GASOLINE PORTABLE SERIES

MANUAL START ENGINE 3000 RPM

Air Cooled

3000 rpm

LWA  
2000/14/CE

HONDA

AVR  
AUTOMATIC  
VOLTAGE  
REGULATOR



G S A



G S A



G S A

	MGTP 3,5 H BM AS	MGTP 4,8 H BM AS AVR	MGTP 4,8 H BM AS
Code	PP58-4M00	PP60-5M00	PP59-5M00
<b>On board control panel equipped with:</b>			
	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket
<b>Generator</b>			
Type	Linz E1C10SD	Linz E1C10SF c/w AVR	Linz E1E10MH
Power	<b>3,5 kVA 230V</b>	<b>4,8 kVA 230V</b>	<b>4,8 kVA 230V</b>
Frequency	50 Hz	50 Hz	50 Hz
<b>Engine</b>			
	<b>HONDA</b>	<b>HONDA</b>	<b>HONDA</b>
Engine type	GX160	GX270	GX270
N° cylinders	1	1	1
Power	4,8 HP	8,4 HP	8,4 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline	Unleaded gasoline
Starting system	Manual recoil	Manual recoil	Manual recoil
<b>Dimensions &amp; weight</b>			
Fuel tank capacity	3,1 lt	5,3 lt	5,3 lt
Running Time	2,8 hrs	2,7 hrs	2,7 hrs
Dry weight	47 Kg	71 Kg	71 Kg
Dimensions (L. x W. x H.)	620 x 440 x 540 mm	760 x 520 x 620 mm	760 x 520 x 620 mm

## Options

- ⊙ Site tow trailer
- ≡⊙ Road tow trailer
- ⊙ Trolley

## Legend

G	Gasoline	S	Single phase	A	Air cooled
D	Diesel	T	Three phase	W	Water cooled