

# GASOLINE PORTABLE SILENCED SERIES

AIR COOLED ENGINE 3000 RPM

Air Cooled

3000 rpm

LWA  
2000/14/CE

HONDA



G S A

G T A

	MGTP 6 AE	MGTP 7 AE 3F
Code	PP77-6MSO	PP78-7TSO
<b>On board control panel equipped with:</b>		
	<ul style="list-style-type: none"> <li>- Hour counter</li> <li>- Volt meter</li> <li>- Circuit breaker</li> <li>- Emergency Stop</li> <li>- Low oil pressure signal lamp</li> <li>- Soundproof canopy</li> <li>- Exhaust gas silencer</li> <li>- Battery charger</li> <li>- Low Fuel</li> <li>- 2x32A 1ph 230V EEC socket</li> <li>- 1x16A 1ph 230V EEC socket</li> </ul>	<ul style="list-style-type: none"> <li>- Hour counter</li> <li>- Volt meter</li> <li>- Circuit breaker</li> <li>- Emergency Stop</li> <li>- Low oil pressure signal lamp</li> <li>- Soundproof canopy</li> <li>- Exhaust gas silencer</li> <li>- Battery charger</li> <li>- Low Fuel</li> <li>- 1x 16A 3Ph 400V EEC socket</li> <li>- 1x 32A 1Ph 230V EEC socket</li> <li>- 1x 16A 1Ph 230V EEC socket</li> </ul>
<b>Generator</b>		
Type	Linz E1C10 M H	Linz E1S10M H
<b>Power</b>	<b>6 kVA 230V</b>	<b>7 kVA 400V</b>
Frequency	50 Hz	50 Hz
<b>Engine</b>		
	<b>HONDA</b>	<b>HONDA</b>
Engine type	GX390	GX390
N° cylinders	1	1
Power	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
<b>Dimensions &amp; weight</b>		
Fuel tank capacity	21 lt	21 lt
Running Time	7 hrs	7 hrs
Dry weight	190 Kg	190 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

## Options

- Site tow trailer
- ≡● Road tow trailer
- Trolley

## Legend

<b>G</b>	Gasoline	<b>S</b>	Single phase	<b>A</b>	Air cooled
<b>D</b>	Diesel	<b>T</b>	Three phase	<b>W</b>	Water cooled