

GASOLINE PORTABLE SILENCED SERIES

AIR COOLED ENGINE 3000 RPM

Air Cooled

3000 rpm

LWA
2000/14/CE

HONDA



G S A

G T A

	MGTP 6 AE	MGTP 7 AE 3F
Code	PP77-6MSO	PP78-7TSO
On board control panel equipped with:		
	<ul style="list-style-type: none"> - Hour counter - Volt meter - Circuit breaker - Emergency Stop - Low oil pressure signal lamp - Soundproof canopy - Exhaust gas silencer - Battery charger - Low Fuel - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket 	<ul style="list-style-type: none"> - Hour counter - Volt meter - Circuit breaker - Emergency Stop - Low oil pressure signal lamp - Soundproof canopy - Exhaust gas silencer - Battery charger - Low Fuel - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket - 1x 16A 1Ph 230V EEC socket
Generator		
Type	Linz E1C10 M H	Linz E1S10M H
Power	6 kVA 230V	7 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
	HONDA	HONDA
Engine type	GX390	GX390
N° cylinders	1	1
Power	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Dimensions & weight		
Fuel tank capacity	21 lt	21 lt
Running Time	7 hrs	7 hrs
Dry weight	190 Kg	190 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

Options

- Site tow trailer
- ≡● Road tow trailer
- Trolley

Legend

G	Gasoline	S	Single phase	A	Air cooled
D	Diesel	T	Three phase	W	Water cooled