

S-EVENT 10



Water Cooled

DIESEL

Three phase

Kubota

1500 rpm

LWA
2000/14/CE

Noise level in compliance with directive 2000/14/CE



S-EVENT 10

Code	RP31-10TSO	
Generator		
Type	Linz E1X13S C/4	
Power	10 kVA 400V	
Frequency	Hz	50
Cosφ	0.8	
Insulation class	H	
Mechanical protection	IP23	
Engine Kubota		
Engine type	D1105	
N° cylinders	3	
Displacement	cm ³	1123
Power	HP	13.7
Engine speed	r.p.m.	1500
Speed regulation	Mechanical	
Cooling	Water	
Fuel	Diesel	
Oil sump capacity	lt.	5.1
Starting system	Electric	
Specific fuel consumption	gr/kWh	265
Dimensions & weight		
Noise level	dBA at 7mt	55
Battery	V	12
Fuel tank capacity	lt	300
Average operating hours	hrs	92
Length	mm	1866
Width	mm	795
Height	mm	1525
Dry weight	Kg	810

DISTRIBUTION PANEL:

1x 32A 3Ph 400V EEC socket
1x 32A 1Ph 230V EEC socket
1x 16A 1Ph 230V EEC socket
400V 3Ph hard wires protected by safety switch

STANDARD FEATURES:

Super silenced canopy Lwa
Super silenced exhaust gas silencer
Built in fuel tank
Bunded tank
12v battery
Battery switch
Forklift pocket
Central lifting eye
Heavy bump stoppers
3 ways valve for external fuel tank connection
Gateway with external antenna

Options

- ☉ Site tow trailer
- ☉ Road tow trailer

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 401
ON/OFF switch
Safety cover for DSE 401 and circuit breakers
Circuit breaker
Earth leakage circuit breaker
Remote start/stop connector
Emergency stop