

Water Cooled

DIESEL

Three phase

Kubota

1500 rpm



Noise level in compliance with directive 2000/14/CE



S-EVENT 20		
Code	RP46-20TS0	
<b>Generator</b>		
Type	Linz Pro 185A4	
<b>Power</b>	<b>20 kVA 400V</b>	
Frequency	Hz	50
Cosφ	0.8	
Insulation class	H	
Mechanical protection	IP23	
<b>Engine</b>		
Engine type	V2203	
N° cylinders	4	
Displacement	cm <sup>3</sup>	2197
Power	HP	27
Engine speed	r.p.m.	1500
Speed regulation	Mechanical	
Cooling	Water	
Fuel	Diesel	
Oil sump capacity	lt.	7.6
Starting system	Electric	
Specific fuel consumption	l/h	6
<b>Dimensions &amp; weight</b>		
Noise level	dBA at 7mt	55
Battery	V	12
Fuel tank capacity	lt	300
Average operating hours	hrs	44.5
Length	mm	2300
Width	mm	850
Height	mm	1600
Dry weight	Kg	1250

#### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 401
ON/OFF switch
Safety cover for DSE 401 and circuit breakers
Circuit breaker
Earth leakage circuit breaker
Remote start/stop connector
Emergency stop

#### Options

- Site tow trailer
- Road tow trailer

#### DISTRIBUTION PANEL:

1x 32A 3Ph 400V EEC socket
1x 32A 1Ph 230V EEC socket
1x 16A 1Ph 230V EEC socket
400V 3Ph hard wires prtected by safety switch

#### STANDARD FEATURES:

Super silenced canopy Lwa
Super silenced exhaust gas silencer
Built in fuel tank
Bunded tank
12v battery
Battery switch
Forklift pocket
Central lifting eye
Heavy bump stoppers
3 ways valve for external fuel tank connection
Gateway with external antenna